



STAINLESS STEEL CAMLOCK COUPLING

Material : Stainless Steel

Gasket : NBR

Safety Pin : Steel Standard : MIL A-A59326 / EN14420-7(DIN2828)

Surface Finish : Shotting

Method : Stainless steel

Thread : ISO228(BSPP) ISO7(BSPT) ANSI B1.20

STYLE	SIZE	CODE	STYLE	SIZE	CODE
	1/2" (DN15)	FIT A050-316 (DN15)BSPP		1/2" (DN15)	FIT E050-316 (DN15)
	3/4"(DN20)	FIT A075-316 (DN20)BSPP		3/4"(DN20)	FIT E075-316 (DN20)
	1"(DN25)	FIT A100-316 (DN25)BSPP		1"(DN25)	FIT E100-316 (DN25)
	1-1/4"(DN32)	FIT A125-316 (DN32)BSPP		1-1/4"(DN32)	FIT E125-316 (DN32)
	1-1/2"(DN40)	FIT A150-316 (DN40)BSPP		1-1/2"(DN40)	FIT E150-316 (DN40)
	2"(DN50)	FIT A200-316 (DN50)BSPP		2"(DN50)	FIT E200-316 (DN50)
	2-1/2"(DN65)	FIT A250-316 (DN65)BSPP		2-1/2"(DN65)	FIT E250-316 (DN65)
	3"(DN80)	FIT A300-316 (DN80)BSPP		3"(DN80)	FIT E300-316 (DN80)
MALE ADAPTER	4"(DN100)	FIT A400-316 (DN100)BSPP	MALE ADAPTER	4"(DN100)	FIT E400-316 (DN100)
X	5"(DN125)	FIT A500-316 (DN125)BSPP	X	5"(DN125)	FIT E500-316 (DN125)
FEMALE THREAD	6"(DN150)	FIT A600-316 (DN150)BSPP	HOSE SHANK	6"(DN150)	FIT E600-316 (DN150)
STYLE	SIZE	CODE	STYLE	SIZE	CODE
	1/2" (DN15)	FIT B050-316 (DN15)BSPT		1/2" (DN15)	FIT F050-316 (DN15)BSPT
	3/4"(DN20)	FIT B075-316 (DN20)BSPT		3/4"(DN20)	FIT F075-316 (DN20)BSPT
	1"(DN25)	FIT B100-316 (DN25)BSPT		1"(DN25)	FIT F100-316 (DN25)BSPT
	1-1/4"(DN32)	FIT B125-316 (DN32)BSPT		1-1/4"(DN32)	FIT F125-316 (DN32)BSPT
	1-1/2"(DN40)	FIT B150-316 (DN40)BSPT		1-1/2"(DN40)	FIT F150-316 (DN40)BSPT
	2"(DN50)	FIT B200-316 (DN50)BSPT		2"(DN50)	FIT F200-316 (DN50)BSPT
	2-1/2"(DN65)	FIT B250-316 (DN65)BSPT		2-1/2"(DN65)	FIT F250-316 (DN65)BSPT
	3"(DN80)	FIT B300-316 (DN80)BSPT		3"(DN80)	FIT F300-316 (DN80)BSPT
FEMALE COUPLING	4"(DN100)	FIT B400-316 (DN100)BSPT	MALE ADAPTER	4"(DN100)	FIT F400-316 (DN100)BSPT
X	5"(DN125)	FIT B500-316 (DN125)BSPT	X	5"(DN125)	FIT F500-316 (DN125)BSPT
MALE THREAD	6"(DN150)	FIT B600-316 (DN150)BSPT	MALE THREAD	6"(DN150)	FIT F600-316 (DN150)BSPT



STAINLESS STEEL CAMLOCK COUPLING

Material : Stainless Steel

Gasket : NBR

Safety Pin : Steel Standard : MIL A-A59326 / EN14420-7(DIN2828)

Surface Finish : Shotting

Method : Stainless steel

Thread : ISO228(BSPP) ISO7(BSPT) ANSI B1.20

STYLE	SIZE	CODE	STYLE	SIZE	CODE
	1/2" (DN15)	FIT C050-316 (DN15)		1/2" (DN15)	FIT DC050-316 (DN15)
	3/4"(DN20)	FIT C075-316 (DN20)		3/4"(DN20)	FIT DC075-316 (DN20)
	1"(DN25)	FIT C100-316 (DN25)		1"(DN25)	FIT DC100-316 (DN25)
	1-1/4"(DN32)	FIT C125-316 (DN32)		1-1/4"(DN32)	FIT DC125-316 (DN32)
	1-1/2"(DN40)	FIT C150-316 (DN40)		1-1/2"(DN40)	FIT DC150-316 (DN40)
	2"(DN50)	FIT C200-316 (DN50)		2"(DN50)	FIT DC200-316 (DN50)
	2-1/2"(DN65)	FIT C250-316 (DN65)		2-1/2"(DN65)	FIT DC250-316 (DN65)
	3"(DN80)	FIT C300-316 (DN80)		3"(DN80)	FIT DC300-316 (DN80)
FEMALE COUPLING	4"(DN100)	FIT C400-316 (DN100)	DUST CAP	4"(DN100)	FIT DC400-316 (DN100)
X	5"(DN125)	FIT C500-316 (DN125)		5"(DN125)	FIT DC500-316 (DN125)
HOSE SHANK	6"(DN150)	FIT C600-316 (DN150)		6"(DN150)	FIT DC600-316 (DN150)
STYLE	SIZE	CODE	STYLE	SIZE	CODE
	1/2" (DN15)	FIT D050-316 (DN15)BSPP		1/2" (DN15)	FIT DP050-316 (DN15)
	3/4"(DN20)	FIT D075-316 (DN20)BSPP		3/4"(DN20)	FIT DP075-316 (DN20)
	1"(DN25)	FIT D100-316 (DN25)BSPP		1"(DN25)	FIT DP100-316 (DN25)
	1-1/4"(DN32)	FIT D125-316 (DN32)BSPP		1-1/4"(DN32)	FIT DP125-316 (DN32)
	1-1/2"(DN40)	FIT D150-316 (DN40)BSPP		1-1/2"(DN40)	FIT DP150-316 (DN40)
	2"(DN50)	FIT D200-316 (DN50)BSPP		2"(DN50)	FIT DP200-316 (DN50)
	2-1/2"(DN65)	FIT D250-316 (DN65)BSPP		2-1/2"(DN65)	FIT DP250-316 (DN65)
	3"(DN80)	FIT D300-316 (DN80)BSPP		3"(DN80)	FIT DP300-316 (DN80)
FEMALE COUPLING	4"(DN100)	FIT D400-316 (DN100)BSPP	DUST PLUG	4"(DN100)	FIT DP400-316 (DN100)
X	5"(DN125)	FIT D500-316 (DN125)BSPP		5"(DN125)	FIT DP500-316 (DN125)
FEMALE THREAD	6"(DN150)	FIT D600-316 (DN150)BSPP		6"(DN150)	FIT DP600-316 (DN150)