

Series
BT60/BT120/BT240



FC KC CE

New Generation, Bluetooth-Enabled Automatic Lubricator.



Pulsarlube **BT**

Features & Advantages

- Advanced Convenience** Conveniently control the lubricator using the Pulsarlube mobile App

- Enhanced User-Friendliness** Easily monitor nearby lubricators within a close proximity of your mobile (proximity pairing)
Possible to change mode settings while lubricators are in operation

- Integrated DB Management** Easily share DB between mobile device and server

- Safe Working Environment** Remotely monitor lubricator status in hazardous and inaccessible work areas via mobile App in close proximity

- Outstanding Performance**
 - High output pressure enables remote installation up to 6m (20ft)
 - Various grease pouch capacity and lubricant type available
 - Ingress Protection Rating : IP65

Typical Applications



- Where maintenance access is not easy
- Where a cluster of bearings is located in close proximity (Paper, Steel, Cement or Food Industry)
- Where lubrication management is tedious and inconvenient

Details

Product Details



Grease Pouch Capacity
60ml / 120ml / 240ml (pre-set)

Power Supply
DC 4.5V Battery Pack (replaceable)
Standard : Alkaline Battery
Optional : Lithium Battery

Operating Pressure
30 ~ 60bar (435~870psi)

Operating Temperature
Standard Alkaline Battery :
-5 ~ 60 (23°F ~ 140°F)
Optional Lithium Battery :
-20 ~ 60 (-4°F ~ 140°F)

Dispensing Periods
1, 2, 3...10, 11, 12 month

Remote Installation
Max. 6m (20ft) with Ø6 tube
Multi-Point Installation
Max. 3m (10ft) with Ø6 tube (Up to 8 points)

Dispensing Volume
0.34ml/stroke (@ 20/68°F)

Product Certifications & IP Code
CE / KC / FCC / IP65

Detection Range
5 ~ 20m depending on installation environment

Bluetooth Specifications
Bluetooth 4.1 (class 2)

Rev.00



PNEUMAX CO., LTD

107/1 Chaloen Phrakiat R.9 Rd., Pravet, Bangkok 10250, Thailand.
Tel. +66 2726 8000 Fax. +66 2726 8266-9
E-mail. sales.air@pneumax.co.th www.pneumax.co.th

